

ULA Series Online Smart Rack Mount UPS

1KVA ~ 3KVA 1 phase

PF 0.9




Features


- High frequency true on-line double conversion technology
- DSP (Digital signal processing) control technology
- Active power factor correction (APFC), input power factor up to 0.99
- Output power factor 0.9
- Wide input voltage range (110 V ~ 300 Vac) and frequency range (40 ~ 70 Hz)
- Auto sensing frequency
- 50 / 60 Hz frequency conversion
- Cold start
- Rear ventilation design and variable speed fan
- Effective software and hardware protection
- Quick and stable charging, 90% capacity restored in 3h (standard model UPS)
- Linear derating in low voltage input reducing battery discharging times
- Settable delayed start when power is restored
- Hot-swappable battery
- Advanced battery management (ABM)
- Multiple functions settable via LCD: output voltage, EOD, auto-start, bypass mode
- Multi-platform communications: RS232 (standard), USB / RS485 / SNMP / dry contacts (optional)
- Software: UPS monitoring & system auto restart and shutdown via RS232 (standard). Web browser management by IP (LAN) via SNMP (optional)
- Optional USB, RS485 card, AS400 dry contacts, SNMP card, SMS alarms, EPO function, MBS (External maintenance bypass switch)

Rear Panel


1. AC input socket
2. Battery connector (Optional)
3. Fan
4. USB (Optional)
5. EPO (Optional)
6. RS232
7. Intelligent slot (Optional)
8. Output sockets




1kVAS



2kVAS



3kVAS



Easy for maintenance, hot-swappable battery

Specifications

Online Transformerless UPS

MODEL	ULA102RT				ULA202RT				ULA302RT			
Capacity	1kVA / 900W				2kVA / 1800W				3kVA / 2700W			
INPUT												
1 PHASE (1P + N + PE)												
Rated voltage	208 / 220 / 230 / 240 Vac											
Voltage range	110Vac – 300Vac depending on loads connected											
Frequency	50Hz or 60Hz (40Hz – 70Hz auto sensing)											
Power factor	≥ 0.99											
Bypass voltage range	-25% ~ +15% (settable)											
Total harmonic distortion	≤ 6%											
OUTPUT												
1 PHASE (1P + N + PE)												
Voltage	208 / 220 / 230 / 240 Vac (settable via LCD)											
Voltage regulation	± 1%											
Frequency	50Hz or 60Hz ± 1% (Line mode) ; 50Hz or 60Hz ± 0.05Hz (Battery mode)											
Waveform	Pure Sine Wave											
Power factor	0.9											
Total harmonic distortion (THDv)	≤ 2% (linear load); ≤ 5% (non-linear load)											
Crest factor	3:1											
Overload	105% ~ 125% for 1 min, 125% ~ 150% for 30 s, > 150% for 300 ms											
BATTERIES												
DC voltage	24V (S)	24V (H)	36V (S)	36V (H)	48V (S)	48V (H)	72V (S)	72V (H)	72V (S)	72V (H)	96V (S)	96V (H)
Inbuilt battery	2×9Ah	/	3×7Ah	/	4×9 Ah	/	6×7 Ah	/	6×9 Ah	/	8×7 Ah	/
Charging current (max.)	Standard model: 1A, Long time model: 6A											
Recharger time	Standard model: 90% capacity restored in 3 hours; Long time model: depend on the capacity of battery											
Back-up time	7 minutes (100% load) / 15 minutes (50% load)											
SYSTEM												
Efficiency	≥ 90% (Mains mode)				≥ 91% (Mains mode)				≥ 92% (Mains mode)			
	≥ 85% (Battery mode)				≥ 86% (Battery mode)				≥ 87% (Battery mode)			
	≥ 95% (ECO mode)				≥ 96% (ECO mode)				≥ 97% (ECO mode)			
Transfer time	Mains mode to battery mode: 0 ms Inverter mode to bypass mode: 4 ms (typical)											
Protections	Short-circuit, overload, overtemperature, battery discharge protection and fan testing protection											
Communications	RS232 (standard) or USB; RS485 (Optional) with UPSmart software for monitoring & system shutdown / SNMP with iStar software for monitoring & system shutdown via LAN (Optional)											
Display	LCD + LED											
Standards	EN 62040-1, EN 62040-2, EN 61000-3-2, EN 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, IEC 61000-2-2, IEC 62040-2, IEC 62040-1											
OTHERS												
Operating temperature	0℃ ~ 40℃											
Storage temperature	-25℃ ~ 55 °C (without batteries)											
Relative humidity	0~95% (non-condensing)											
Altitude	≤ 1000 m, derating 1% for each additional 100 m											
IP rating	IP 20											
Noise level at 1m	≤ 50 dB											
Dimensions (W × D × H) (mm)	440 ×338 ×88	440 ×468 ×88	440 ×430 ×88	440 ×468 ×88	440 ×430 ×88	440 ×468 ×88	440 ×560 ×88	440 ×468 ×88	440 ×560 ×88	440×468×88(UPS) 440×468×88(BAT)		440 ×468 ×88
Packaged dimensions (W×D×H) (mm)	545 ×428 ×194	545 ×592 ×198	545 ×560 ×201	545 ×592 ×201	545 ×560 ×201	545 ×782 ×201	545 ×690 ×201	545 ×592 ×201	545 ×690 ×201	545 ×592 ×198	592x545 x198 (UPS) 597x545 x198 (BAT)	545 ×592 ×201
Net weight(kg)	10.6	7.6	15.5	7.6	18.7	9.7	25.6	9.7	26.8	10	9.45(UPS) 27.2(BAT)	10.1
Gross weight(kg)	11.3	11	18.6	11.1	21.8	14	25.8	13.2	29.7	13.5	12.97(UPS) 30.2(BAT)	13.6

•Derate capacity to 70% in CUCF mode and to 90% when the output voltage is adjusted to 208 Vac.
•S means standard model, H means long time model.

•All specifications are subject to change without notice.
•Custom-made specifications are acceptable.

Up Select Electronics Co., Ltd.

No.14, Aly. 2, Ln. 595, Bei'an Rd., Zhongshan Dist., Taipei City 104, Taiwan (R.O.C.)

Tel: +886-963367802 * Home: www.upselect.com