

MODEL	UDU2500
PICTURE	
CAPACITY	2500VA/1500W
TECHNOLOGY	Line-Interactive
INPUT	
Normal voltage	220/230/240VAC
Voltage range	160VAC - 295VAC
Frequency	50Hz $\pm$ 5Hz or 60Hz $\pm$ 5Hz (Auto Sense)
Cable Plug Type	German power plug*1pc
OUTPUT	
Normal voltage	220/230/240VAC
Voltage Regulation	$\pm$ 10%
Frequency	50Hz $\pm$ 1Hz or 60Hz $\pm$ 1Hz
THD	<1% (linear load), <5% (non-linear load)
Waveform	Modified Sine wave
Steps of Regulation	Yes (1-step boost + 1-step buck)
Output Sockets	Schuko outlet*6pcs for Back-up & Surge protected 
BATTERY	
DC Voltage	48VDC
Type	YUASA Battery - Valve Regulated Sealed Lead Acid (VRLA) ; Maintenance free
Capacity	12V/9AH x 4 PCS
Back-up time	> 40 minutes for PC of standard PC with load at 150W
DISPLAY	
LCD	Display: Input voltage, Output voltage, Load level, Battery level, Fault, Battery fail, Overload, AC normal
FUNCTION	
Overload Protection	YES
Short Circuit Protection	AC fuse and Electronics Circuit
Auto-recharge	YES
Auto-restart	YES
MANAGEMENT	
USB Communication Port	Yes, USB cable + download software included
Dry contact	Optional
ENVIRONMENT	
Temperature	0° C - 40° C
Humidity	<95% (Non-condensing)
Acoustic Noise	<40dB khoảng cách 1m
PHYSICAL	
Cabinet Material	Iron Cabinet
Dimension(D*W*H)	390 x 182 x 285mm
ACCESSORIES	All of accessories included + User Manual
Remark	* Made in Taiwan R.O.C.
	* Warranty within 2 years including batteries
	* Product specifications are subject to change without further notice